

CLAIMS

1. A disk playback device comprising a calculation
processing circuit for determining an optimum value of offset
5 for an error signal based on an amplitude value of the error
signal in accordance with focus deviation or tracking
deviation of an optical head or an amplitude value of an
output signal of the optical head, and making an offset
adjustment based on the optimum offset value, the calculation
10 processing circuit approximating to a quadratic curve the
relationship between offset values and the amplitude values
in signal reproduction, and repeating calculation of the
optimum offset values based on the quadratic curve, and
comprising:

15 calculation processing means for approximating to a
quadratic curve the relationship between the offset values
and the amplitude values with reference to three different
offset values and three amplitude values at the respective
offset values, and calculating an offset value corresponding
20 to the peak of the quadratic curve as the optimum offset
value, and

value setting means for setting the three different
offset values: a first offset value; a second offset value
smaller than the first offset value and having an amplitude

value smaller than an amplitude value at the first offset value by a predetermined value or more; a third offset value greater than the first offset value and having an amplitude value smaller than an amplitude value at the first offset

5 value by a predetermined value or more, and setting the three amplitude values respectively at three amplitude values at the first to third offset values,

the value setting means setting the first offset value at an optimum offset value obtained in a previous optimum offset

10 value calculation processing, and setting the second and third offset values respectively at second and third offset values set in a previous optimum offset value calculation processing.

2. A disk playback device according to claim 1 wherein the
15 calculation processing circuit comprises:

first checking means for checking whether an amplitude value at the previous second offset value is smaller than an amplitude value at the previous optimum offset value by a predetermined value or more,

20 second checking means for checking whether an amplitude value at the previous third offset value is smaller than an amplitude value at the previous optimum offset value by a predetermined value or more, the value setting means comprising:

second offset value setting means for retrieving an offset value having an amplitude value smaller than the amplitude value at the previous optimum offset value by a predetermined value or more when the amplitude value at the previous second offset value is not found to be smaller than the amplitude value at the previous optimum offset value by a predetermined value or more, and setting a second offset value at the retrieved offset value, and

third offset value setting means for retrieving an offset value having an amplitude value smaller than the amplitude value at the previous optimum offset value by a predetermined value or more when the amplitude value at the previous third offset value is not found to be smaller than the amplitude value at the previous optimum offset value by a predetermined value or more, and setting a third offset value at the retrieved offset value.

3. A disk playback device according to claim 1 or claim 2 wherein the disk playback device comprises temperature detection means for detecting a temperature of the disk, and the calculation processing circuit calculates the optimum offset value every time the disk is varied in temperature by a predetermined temperature value.